







Digital Hand-held "Pocket" Ethylene Glycol refractometer

Cat.No.4491,4492

## **Application**

The "Pocket" Ethylene Glycol refractometer, PAL-91S and PAL-92S, easily measure the coolant in brine and other agents of Ethylene Glycol. Measured value displayed digitally.

The freezing point of the sample can also be measured and displayed.

### Features

- Calibration with water only
- Measurement in 3 seconds
- Extremely water resistant (IP65)
- Light & Compact, 100g
- Ergonomically designed for easy, one-handed operation
- Convenient storage case
- Automatic Temperature Compensation (ATC)
- Designed with a strap holder option

## Measuring Method



① Place the sample onto the prism surface.



2 Press the START key.



(3) The measurement value will be displayed in 3 seconds.



4 \*Secondary Scale: Press the START kev for 2 seconds while the concentration (%) is indicated, to display the freezing point (°C/°F).

# **Specifications**

	PAL-91S	PAL-92S
Measurement range Concentration of Ethylene Glycol *Main scale Freezing point of Ethylene Glycol *Secondary scale	0.0~90.0% (V/V) 0~-50°C	0.0~90.0% (V/V) 32~-60°F
Resolution Concentration of Ethylene Glycol *Main scale Freezing point of Ethylene Glycol *Secondary scale	0.2% (V/V) 1°C	0.2% (V/V) 1°F
Measurement accuracy Concentration of Ethylene Glycol *Main scale Freezing point of Ethylene Glycol *Secondary scale	±0.4% (V/V) ±1°C	±0.4% (V/V) ±1°F
Measurement temperature	10~40°C (Automatic Tempera	50~104°F ature Compensation)
Sample volume	0.3ml or more	
Measuring time	3 seconds	
International Protection Class	IP65 Water Resistant	
Power supply	2 × AAA Batteries	
Battery life	Approx 11,000 measurements (When an alkaline battery is used)	
Dimensions and weight	55(W) × 31(D) × 109(H)mm, 100g (Main Unit only)	



ATAGO products are acknowledged by HACCP, G.M.P. and G.L.P.





