SOLUTIONS TECHNIQUES pour

laboratoires & industries

LABO AND CO

Nos compétences et services associés



COOLSAFE TOUCH 95-15
SPECIFICATIONS



CoolSafe Touch 95-15	Unit	Part no: 700057
Digital read-out of temperature		Yes
Digital read-out of pressure		Yes
Ultimate temperature at 20°C room temperature	°C	-95
Power requirements	V/Hz	230/50-60
Power consumption	W	1400
Insulation	mm	90
Condenser capacity	kg	10
Condenser capacity per 24 hours	kg	6
Total volume of Condenser	L	15
Weight net	kg	85
Cabinet dimensions (DxWxH)	mm	620x495x745
Cabinet material		Polyester coated steel
Condenser material		Stainless steel AISI 316
Cooling media		R 507/R170
Vacuum Valve		Electric
Draintap		Yes
Touch screen for control options		Yes
USB port for LaboGene software/SD card for data		Yes

LLOYD'S REGISTER · LRQA
ISO 9001
UKAS MANAGEMENT SYSTEMS
001

LABO AND CO
50 avenue de Grosbois
94440 Marolles-en-Brie

Tel : 01 45 98 74 80
Fax : 01 45 98 77 23
contact@laboandco.com

LABO AND CO



Gardez un œil sur laboandco.com

laboandco.com