

#N°1 français du service pour les laboratoires

LABO AND CO


SOLUTIONS TECHNIQUES & SERVICES pour laboratoires & industries

- PLUS DE 35 COLLABORATEURS
- 20 ANS D'EXPÉRIENCE
- UNE COUVERTURE NATIONALE

De l'équipement ET du service !



AMÉNAGEMENT



Chaque laboratoire, entreprise ou industrie a ses enjeux, ses objectifs et ses contraintes. Les aménagements sont donc tous différents pour répondre à des problématiques toujours uniques.


Notre équipe est là pour comprendre votre besoin et vous accompagner au plus près.

Labo and Co est à vos côtés pour l'établissement de votre cahier des charges, pour le suivi des travaux et leur réception et pour fournir le meilleur matériel et le plus haut niveau de service.

DISTRIBUTION

Labo and Co propose **des miliers de références d'équipement**, des plus simples aux plus complexes. Une équipe d'ingénieurs d'affaires et de techniciens, répartis dans toute la France, disposent d'une connaissance approfondie des équipements et mettent leur expérience à votre service. **Avant de conclure toute vente, nous nous assurons d'avoir compris tous vos enjeux.**

Nos partenariats et nos collaborations depuis des années avec l**es plus grandes marques** vous garantissent une qualité sans faille.



SERVICES

- QUALIFICATION & INSTALLATION
- MÉTROLOGIE & ÉTALONNAGE
- RECONDITIONNEMENT
- RÉPARATION & ENTRETIEN
- LOCATION
- ESSAIS EXTERNALISÉS

Chez Labo and Co, nous savons à quel point le dysfonctionnement d'un équipement peut avoir des répercussions catastrophiques sur des recherches ou sur une production. **Notre approche repose sur un éventail très large de services et de compétences nous permettant de répondre à l'ensemble des problématiques que vous pouvez rencontrer.** Que votre besoin soit ponctuel ou récurrent, notre gamme de prestations saura y répondre.

CONTACTEZ-NOUS

+33 1 45 98 74 80 @ contact@laboandco.com www.laboandco.com



Digital video microscope, 400x, achromatic objectives

Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	As optional
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Type	Monocular
	Inclination	45°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	35
	Standard magnifications	40x-400x
	Type	Achromatic
		4x/0.10, W.D. 10.6 mm
		10x/0.25, W.D. 7.0 mm
		40x/0.65, W.D. 0.5 mm
Stage	Type	Double layer
	Rotation	No
	Dimensions (mm)	125x125
	Moving mechanism	Rack and pinion
	Moving range (mm)	62x24
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1

Condenser - Single Position	Type	Abbe
	Numerical aperture (N.A.)	1.25
	Diaphragms	Iris
	Focusable	By rotation

Focusing System	Type	Coaxial coarse & fine
	Coarse total travel (mm)	23
	Fine total travel (per single rotation) (mm)	1,2
	Fine graduations	100
	Fine resolution (µm)	12
	Upper stop to prevent contact	Yes

Transmitted Illumination	Type	LED
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5

Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	Rechargeable batteries	Yes
	Battery type	Ni-MH (3x, AAA size)
	Working time of batteries (hours)	up to 8
	Charging time of batteries (hours)	8

Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)

Product Dimensions	Height (mm)	380
	Width (mm)	135
	Depth (mm)	235

Product Weight	(kg)	2,7

DIGITAL HEAD WITH MONITOR

General specifications	SD Card Still image capture	Yes
	SD Card Video recording	Yes
	Dimensions (mm)	180 x 150 x 90
	Weight (kg)	0.360

Sensor	Camera resolution (n° of pixels: W x H)	1920x1080
	Camera resolution (MP)	2
	Frame rate full resolution (fps)	30@1920x1080
	Color / Monochrome	Color
	Sensor Size	1/2.8"
	Sensor Technology	CMOS
	Sensor Type	MICRON CMOS
	Image Format	16/9
	Pixel Size (µm)	2.9x2.9
	Acquisition technology	Rolling shutter
	Exposure time	0- 33333 µs
	IR filter	Yes
	IR filter range (nm)	680

Monitor	Display size	7"
	Display resolution	1024x600

System Power Supply	Type	External
	Connector	Jack, 2.1 mm
	Power plug type	European
	Input voltage	100/240 Vac, 50/60Hz
	Output voltage	12 Vdc, 1000 mA
	LED indicator	Yes

Available Software	Camera SW	S-Viewer

System accessories	SD card	4GB
	USB SD card reader	Yes